

Groundwater movements around a repository

Rock mechanics analyses

Joe L Ratigan

Hagconsult AB september 1977

GROUNDWATER MOVEMENTS AROUND A REPOSITORY
ROCK MECHANICS ANALYSES

Joe L Ratigan
Hagconsult AB september 1977

Denna rapport utgör redovisning av ett arbete som utförts på uppdrag av KBS. Slutsatser och värderingar i rapporten är författarens och behöver inte nödvändigtvis sammanfalla med uppdragsgivarens.

I slutet av rapporten har bifogats en förteckning över av KBS hittills publicerade tekniska rapporter i denna serie.

TECHNICAL REPORT 4
ROCK MECHANICS ANALYSES

GROUNDWATER MOVEMENTS AROUND A REPOSITORY

Phase 2. Technical report 4. Rock Mechanics Analyses

Hagconsult AB
in association with
Acres Consulting Services Ltd
RE/SPEC Inc.

FOREWORD

This report was prepared as one of a series of Technical reports within a study of the groundwater movements around a repository for radioactive waste in the precambrian bedrock of Sweden. The contract for this study was between KBS - Kärnbränslesäkerhet (Project Fuel Safety) and Hagconsult AB of Stockholm, Sweden. RE/SPEC Inc. of Rapid City, SD/USA and Acres Consulting Services Ltd of Niagara Falls, Ontario/Canada acted as subconsultants to Hagconsult AB.

The principal author of this report is Mr. Joe L. Ratigan of RE/SPEC inc. Review was provided by Dr. Ulf E. Lindblom of Hagconsult AB, Dr. Paul F. Gnirk of RE/SPEC Inc., and Dr Robin G. Charlwood of Acres Consulting Services Ltd.

The opinions and conclusions in this document are those of the author and should not be interpreted as necessarily representing the official policies on recommendations of KBS.

Stockholm September 1977

Ulf E. Lindblom
Study Director
Hagconsult AB

TABLE OF CONTENTS

	<u>Page</u>
1. INTRODUCTION	1
2. ROCK MECHANICS MODELING	2
2.1 Material Characterization	2
2.2 Input Parameters	3
2.3 Repository Modeling	3
3. LOCAL MODELING RESULTS	5
3.1 Model and Assumptions	5
3.2 Pre-emplacement	5
3.3 Post-emplacement	6
3.4 Ventilation effects	8
3.5 Practical Considerations	9
4. GLOBAL MODELING RESULTS	10
4.1 Model and Assumptions	10
4.2 Pre-emplacement	10
4.3 Post-emplacement	10
4.4 Practical Considerations	10
5. SUMMARY AND CONCLUSIONS	

REFERENCES

APPENDIX: FINITE ELEMENT MODELS

LIST OF FIGURES

Figure

1. Local rock mechanics model
2. Regions of strength failure due to excavation in a rock mass with joints at 0° and 90° .
3. Regions of strength failure due to excavation in a rock mass with joints at 45° and -45° .
4. Principle stresses resulting from excavation in a rock mass with $K_o = 2$ and joints at 0° and 90° .
5. Principle stresses resulting from excavation in a rock mass with $K_o = 2$ and joints at 45° and -45° .
6. Progressive strength failure due to excavation and thermomechanical stresses with joints at 0° and 90° .
7. Progressive strength failure due to excavation and thermomechanical stresses with joints at 45° and -45° .
8. In situ, post-excavation and thermomechanical stresses in the storage tunnel roof.
9. In situ, post-excavation and thermomechanical stresses in the storage tunnel rib.
10. In situ, post-excavation and thermomechanical stresses in the storage tunnel floor.
11. Progressive strength failure due to excavation and thermomechanical stresses with joints at 0° and 90° with 30 years of tunnel ventilation.
12. Progressive strength failure due to excavation and thermomechanical stresses with joints at 45° and -45° with 30 years of tunnel ventilation.

13. Global rock mechanics models.
14. Displacement across the earth's surface due to rock mass expansion.
15. Transient displacement above the repository centerline.
16. Horizontal in situ and thermomechanical stresses through the repository centerline.

- A.1.(a) Finite element model for local rock mechanics analysis.
(b) Insert of local rock mechanics model.
- A.2. Finite element model for 500 m repository global rock mechanics analysis.
- A.3. Finite element model for 1000 m repository global rock mechanics analysis.
- A.4. Symmetric half section of finite element model for 500 m linear waste emplacement repository global rock mechanics analysis.

LIST OF TABLES

Table

1. Rock mass properties and in situ conditions.

ROCK MECHANICS ANALYSES OF A RADIOACTIVE WASTE REPOSITORY

1. INTRODUCTION

The determination and rational assessment of groundwater flow around a repository depends upon the accurate analysis of several interdependent and coupled phenomenological events occurring within the rock mass.

In particular, the groundwater flow pathways (joints) are affected by the excavation and thermomechanical stresses developed within the rock mass, and the properties of the groundwater are altered by the temperature perturbations in the rock mass. A detailed discussion of the interrelated coupling phenomena is presented in (1)^x and will not be repeated in its entirety in this report.

The objective of this report is to present the results of the rock mechanics analysis for the repository excavation and the thermally-induced loadings. These results will be used in subsequent studies to assess the perturbations in the groundwater flow pathways resulting from both the excavation and thermally induced loadings and unloadings occurring in the rock. Qualitative analysis of the significance of the rock mechanics results upon the groundwater flow is provided in this report whenever such an analysis can be performed. A quantitative assessment of the rock mechanics results as regards flow permeability perturbations is the subject of a subsequent report (2).

^xNumbers in parenthesis refer to references at end of text.

2. ROCK MECHANICS MODELING

2.1 Material characterization

In an actual rock mass with thermal induced loadings, the material response is non-linear and involves time-dependent deformation and fracture, temperature-dependent thermal, mechanical and hydrological parameters, and intimate coupling of the thermal, mechanical and hydrological occurrences. However, a solution of the total coupled system is difficult, and not practical at the current time. Therefore, in this study, the individual mathematical couplings are being treated separately in an effort to rationally assess the importance of each "coupling", as regards a practical assessment of the groundwater movements around a repository.

In the rock mechanics analysis, the rock properties have been assumed to be temperature and time independent and the interaction of the groundwater pressures within the joints is not considered.

A detailed discussion of the mechanical properties of granitic bedrock, including the expected temperature dependence, is provided in (3).

For the purposes of this analysis, the rock mass is assumed to be well characterized by a linear Mohr Coulomb strength failure criterion. Additionally, the rock is assumed to possess orthogonal joint planes or planes of weakness, failure of which is also of the Mohr Coulomb type. Details of the material characterization employed in this study have been previously described in (4) and (5).

For both the intact rock and the joints, any strength failure is followed by an assignment of a residual strength to the region of failure. For the joints, the residual strength is characterized by a reduced cohesion and internal angle of friction.

For the purposes of this study the strength failure of the rock mass has been assumed to occur on the joint planes or planes of weakness rather than within the intact rock mass. Previous studies (4 and 5) have shown that the assumption of failure along the joints is more conservative than failure within the intact rock.

2.2 Input Data

In order to utilize the material characterization previously described, certain rock mass properties must be selected and in situ conditions assumed. These parameters include rock density, Youngs Modulus, of elasticity, Poisson's ratio, and the coefficient of thermal expansion. In situ conditions which must be selected include the initial virgin stress state, joint orientation and the parameters for the Mohr-Coulomb failure criterion.

The numerical values of these parameters are presented in Table 1. As can be seen in the table all parameters are given only one numerical value with the exception of joint plane orientation which has been given two. Whereas the joints can be expected to be orthogonal and aligned vertically and horizontally, the inclined joint set orientation has been analyzed to illustrate the effects of deviation from vertical and horizontal jointing.

The ratio of virgin horizontal and vertical stresses has been taken to be constant with depth in this study. In fact, this is not the situation indicated in a variety of field investigations, as stated in (3). Generally, field investigations have shown that the horizontal stresses are greater than the vertical stresses at shallow depths. With increasing depth, the ratio of horizontal stress to vertical stress decreases. Therefore, the assumption of a constant ratio of the two stresses results in a conservative assumption due to the fact that horizontal confinement at shallow depths is less in the assumed model than is actually the case in the field.

2.3 Repository Modeling

As was the case in other reports within this study, the modeling of the rock mass containing the repository has been divided into two distinct areas viz; local or near field modeling and global or far field modeling. The local rock mechanics modeling is essential in determining the stress states in the near vicinity of the storage tunnels and canister drill-holes and also in determining the extent of regions of rock which have experienced strength failure due to the excavation and thermal loadings.

The results of this type of modeling can be used directly in determining storage tunnel support requirements (4 and 5). However, in this study the local modeling is being performed for the explicit purpose of assessing the perturbations in the hydraulic permeabilities as a consequence of the excavation and thermomechanical stress states.

The global or far field rock mechanics analysis has been done in an effort to identify areas of potential fracture initiation, and to assess the changes in the hydraulic permeability due to induced thermal stresses.

Both the local and global models are discussed in more detail in further sections of this report, and the finite element meshes are presented in the Appendix. All analysis was performed assuming plane strain in the direction normal to the plane of the model.

3. LOCAL MODELING RESULTS

3.1 Model and Assumptions

The model used for the local rock mechanics analysis is presented in Figure 1. The model has been developed by assuming symmetry about vertical lines through the storage tunnel center and the pillar center. The upper and lower boundaries are positioned at such a distance so as to provide negligible influences upon the local deformations.

Two material types are actually utilized in the analysis of this model. In the region identified as the canister region, the coefficient of thermal expansion is given a zero value, whereas external to this region, the coefficient of thermal expansion is that value given in Table 1. This material differentiation is necessary due to the fact that the temperature fields utilized in determining the thermal loadings are taken directly from those presented in (6). In (6) the actual canister material is modeled in the region identified as the canister region; however, in the rock mechanics analysis, this region must by necessity be the rock situated between adjacent drillholes.

All local rock mechanics analyses were performed without modeling of any storage tunnel backfill material. In this regard, the local analyses is conservative since the backfill may possibly provide some confinement to the storage room periphery.

3.2 Pre-emplacement

The stress states and regions of strength failure which arise due to the excavation of the storage room are obtained by negating the normal stress and tangential shear stress on the storage tunnel periphery which existed prior to excavation. The stress states which then arise in excess of the assumed strength relationship are transferred to adjacent regions which have not yet experienced failure. This process is repeated until all stress states are within a certain tolerance of the residual or intact strength depending on whether the material has failed or not. This "stress-transfer" technique is discussed in (7) and utilized in (4) and (5).

The pre-emplacement analysis was performed for joint sets or planes of weakness at 0 and 90 degrees, and joint-sets at 45 and -45 degrees. Figures 2 and 3 present the regions which have experienced strength failure for each of the respective joint orientations. As can be seen in the figures the two cases do not have a significant amount of "failed region" in common. Therefore, one can conclude that the joint set orientation is an important parameter in the assessment of the pre-emplacement rock mechanics. Storage tunnel support requirements are also highly dependent upon the joint set orientation. Storage room support may be adequately obtained with such measures as shotcrete in the case of the vertical and horizontal joints, whereas the inclined joint set may require rock bolting.

The principle stresses due to the in situ virgin stress and the stresses due to excavation are illustrated in Figures 4 and 5, for both of the respective joint orientations. The resulting stress states for the two orientations are quite similar. Even though the principle stress states are similar, the regions of strength failure differ due to the orientation of the joint sets.

These stress states will be used in subsequent studies to predict the changes in hydraulic permeability caused by the excavation-induced stress changes.

3.3 Post-Emplacement

The post-emplacement stress states and regions of strength failure are determined from both the excavation loadings and the thermal loadings resulting from the radiogenic heat dissipation. In other words, the stress states along with the failed regions from the pre-emplacement analysis are the initial conditions for the calculation of total stresses resulting from the superposition of the incremental thermal loadings. In this regard, the post-emplacement rock mechanics analysis is "quasi-static" and only includes the time dimension implicitly since the incremental thermal loadings represent the various temperatures resulting in time. In particular, the thermal loadings are imposed upon the rock mechanics model as temperatures representative of 0.1, 1, 4, 10, 40, 100 and 1000 years after waste emplacement.

As was the case with the calculation of the excavation stresses, the total stresses resulting from the addition of thermal loading are checked against the strength failure criterion and stress states in excess of the strength are transferred to adjacent locations which have not yet experienced failure. Through this procedure, the progressive strength failure around the storage tunnel can be examined.

Figures 6 and 7 illustrate the progressive strength failure around a storage tunnel for the 0 and 90 degree joint sets and the 45 and -45 degree joint sets, respectively. For both joint set orientations, the additional strength failure due to the thermal loading is not as great as the area of failure due to excavation.

In addition to observing the areal extent of the strength failure one should also note the locations of the strength failure. In the case of the vertical and horizontal joint sets, the strength failure arising from the addition of thermomechanical stress is in the region of the tunnel floor and rib-floor intersection. In the case of the inclined joint sets, the strength failure in excess of that due to excavation occurs for the most part above the tunnel springline. In general, this behavior can be mainly attributed to the shape of the storage tunnel cross section. In other words, the strength failure occurs in regions where the tunnel periphery (and subsequently, principle stresses) are aligned with the joint set orientation. Thus, the geometry of the storage tunnel should be considered once the in situ joint characterization has been established in order to control the strength failure in locations where it may be undesirable. Since the regions near the tunnel periphery which undergo strength failure will undergo dilatation, the hydraulic permeability in these regions could be expected to be much greater than that in the unfailed regions. The porosity could also be expected to be greater.

Figures 8, 9 and 10 illustrate the horizontal and vertical stresses in the roof, rib and floor. The in situ, post-excavation and total stresses after 40 years without ventilation are displayed in the figures. From observation of these figures, qualitative observations of hydraulic permeability changes can be made. Specifically, in the roof, the horizontal permeability

near the tunnel will increase due to the low vertical stress and the vertical permeability will decrease due to the increased horizontal stress. The converse is true at the pillar rib. In the region of the floor, the vertical permeability will probably not decrease as much as will be the case in the roof. The fact that the horizontal stress increase in the floor is not as great as in the roof can again be attributed to the cross sectional shape of the storage tunnel.

3.4 Ventilation Effects

In the previous discussion of post-emplacement stress states and strength failure, the thermal loading was extracted from (6) for the case of no ventilation of the storage tunnels. In this section of the report the thermal loading will be that which is presented in (6) for the case of 30 year ventilation.

In analyzing ventilation from a rock mechanics viewpoint, the primary concern is with the associated strength failure for both the ventilated and unventilated cases. In the present study, the concern in analyzing both ventilated cases and unventilated cases is identical. The regions experiencing strength failure are important in assessing hydraulic permeability changes. Therefore, it is important to identify whether the lack of ventilation results in excessive strength failure or whether the "double thermal cycle" (6) resulting from a finite period of ventilation is, in fact, more detrimental to the tunnel periphery.

Figures 11 and 12 illustrate the progressive strength failure which occurs with 30 years of ventilation for the 0 and 90 degree joint sets and the 45 and -45 degree joint sets. The general features displayed in these figures are similar to those shown in Figures 6 and 7; however, the areal extent of the regions experiencing failure is less with ventilation than without. This is particularly the case with the inclined joint set wherein, the roof experiences considerably less strength failure with ventilation than without. In the case of the horizontal and vertical joint sets, the effect of ventilation is not nearly as pronounced.

3.5 Practical Considerations

In assessing the local response of a rock mass to excavation and thermally-induced loading, physical situations and conditions which are not always amenable to mathematical modeling must be realized when analyzing the results of a mathematical model. For example, rock damage due to excavation methodology is not taken into account in this present study. Additionally, dissimilarity of joint response and strength is not accounted for. Rather, each joint plane is assumed to respond to load in exactly the same manner as each of the other joints and also to have the same strength characteristics.

The exclusion of the later two physical situations (blasting damage and joint set characterization) in the mathematical modeling is natural when site specific properties and conditions are not available. When these properties and conditions do become available, the analysis must be examined and performed again if the investigated physical situations are not within the bounds of the previous modeling.

4. GLOBAL MODELING RESULTS

4.1 Model and Assumptions

Three distinct models were examined for the global rock mechanics analysis. These models are illustrated in Figure 13. Models A and B represent symmetric half sections of repositories situated at 500 meters deep and 1000 meters deep, respectively. The thermal loading for these two models is calculated with the temperatures resulting from instantaneous waste emplacement (6). The temperatures resulting from a 30 year linear waste emplacement were utilized in determining the thermal loading for model C.

Each of the models is homogeneous and the detail of storage room excavation is not provided in the analysis due to the large extent of the models.

4.2 Pre-Emplacement

Since the repository storage tunnel excavation is not modeled in the global analysis, the pre-emplacement stress states are merely the in situ stress states. Determination of the in situ stress state is, however, not necessarily straightforward. Results of several field investigations are presented in (3) which show a tendency for the horizontal stresses to be greater than the vertical for shallow depths and approximately equal to the vertical at much greater depth. The vertical stress is generally assumed to be that which results from assuming a gravitating medium (density times depth). In this analyses the vertical in situ stress is taken to be density times depth and the horizontal in situ stress is assumed to be a constant multiple (=2.0) times the vertical.

4.3 Post-Emplacement

The post-emplacement stress states and regions of strength failure in the global analysis are determined from the superposition of the in situ stresses and those resulting from the respective thermal loadings. As was the case with the local rock mechanics analysis, the time dimension is only implicitly incorporated in the analysis by virtue of the transient thermal loading. In the case of the global analysis, the thermal loadings are imposed upon the rock mechanics model as temperatures representative of 1, 10, 40, 70, 100 and 1000 years after emplacement. Analysis of Model C also involved the thermal loading represented by the temperature field at 5000 years after emplacement. This temperature distribution was calculated using the analytical representation of the heat generating function from (6) for times greater than 1000 years.

In four of the six cases analyzed (3 models x 2 joint sets), minor strength failure occurred at the ground surface above the repository. Model B did not experience any strength failure. However, this strength failure is not of a great concern since the confining horizontal stress which can be expected to exist in the Fennoscandinavian Shield (3) was not modeled. Rather, the ratio of in situ horizontal to in situ vertical stress is taken to be constant at all depths. If the confining horizontal stress were incorporated into the models, no strength failure would be exhibited in any of the global models. Therefore, in a practical sense, the global response of the rock mass to the radiogenic heat dissipation and associated thermal loading is elastic and reversible as far as rock mechanics is concerned.

Models A and C exhibited very similar response. The difference in the thermal loading associated with instantaneous waste emplacement and linear waste emplacement (6) is not significant in the global rock mechanics analysis for the gross thermal loading being considered in Sweden. The upward displacement across the earth's surface at various times for these two models is displayed in Figure 14. The transient displacement above the repository centerline is illustrated in Figure 15. The upward displacement depicted in these figures is not particularly significant. This is particularly true when one notes that the rate of surface uplift due to the rock expansion is about 0.3 mm/yr for the first 100 years and about 0.05 mm/yr from 100 to 1000 years.

These uplift rates can be compared to a current rate of ground surface uplift of 8 mm/year near Luleå and Piteå and 4mm/year near Stockholm (8).

Since the rock mass exhibits no strength failure, one can assume the stress increases to be relatively small. The maximum thermoelastic stresses exhibited in the 500 meter repository simulations are presented in Figure 16 as a function of depth. The thermoelastic stress increases in the 1000 meter repository model are similar to those in the 500 meter model. The displacements at the ground surface have a smoother variation across the ground surface due to a more uniform heating of the rock mass. The maximum uplift for the 1000 meter model is approximately 5 cm.

4.4 Practical Considerations

As was the case with the local analysis and excavation modeling, physical situations and conditions in the global repository domain are not amenable to modeling or prediction. In particular, major structural discontinuities which are site specific cannot be modeled without detailed knowledge of the site subsurface. Additionally, when one reports predictions for time domains of thousands of years, the boundary conditions will be somewhat altered in a relatively unpredictable manner.

Therefore, the global rock mechanics analysis can only be treated as an approximation to the mechanical response of the rock to the thermal loading and not as an exact representation of the rock mass after tens of thousands of years.

5. SUMMARY AND CONCLUSIONS

Non-linear rock mechanics calculations have been completed for the repository storage tunnels and the global repository domain. The rock mass has been assumed to possess orthogonal joint sets or planes of weakness with finite strength characteristics.

In the local analyses of the repository storage tunnels the effects of joint orientation and repository ventilation have been examined. The local analyses indicated that storage room support requirements and regions of strength failure are highly dependent upon joint orientation. The addition of storage tunnel ventilation was noted to reduce regions of strength failure, particularly during the 30 year operational phase of the repository. Examination of the local stresses around the storage tunnels indicated the potential for perturbed hydraulic permeabilities. The permeabilities can be expected to be altered to a greater degree by the stresses resulting from excavation than from stresses which are thermally induced.

The global rock mechanics did not incorporate the excavation of the storage tunnels due to the large areal extent of the models. Subsequently, due to the relatively small thermal stresses which develop with the low gross thermal loading being considered in Sweden, the global models exhibited a reversible elastic response to the radiogenic heat dissipation. The thermal loading provided by the instantaneous waste emplacement resulted in stress states and displacements quite similar to those provided by the linear waste emplacement sequence.

The stress states observed in the local and global rock mechanics models will be used in subsequent studies to quantitatively analyse the perturbations of the hydraulic permeabilities.

REFERENCES

1. Lindblom, U.E., Gnirk, P.F., Charlwood, R.G. and Cherry, J., "GROUNDWATER MOVEMENTS AROUND A REPOSITORY", Phase 1. State of the art and detailed study plan", Submitted to KBS - Kärnbränslesäkerhet, Stockholm, Sweden, 1977.
2. Ratigan, J.L, "GROUNDWATER MOVEMENTS AROUND A REPOSITORY, Phase 2. Technical Report 5. Repository Domain Groundwater flow Analyses - Part I: Permeability Perturbations", To be submitted to KBS - Kärnbränslesäkerhet, Stockholm, Sweden, 1977.
3. Stille, H., Burgess, A.S. and Lindblom, U.E., "GROUNDWATER MOVEMENTS AROUND A REPOSITORY, Phase 2. Technical Report 1. Geological and Geotechnical Conditions", To be submitted to KBS - Kärnbränslesäkerhet, Stockholm, Sweden, 1977.
4. Mahtab, M.A. and Ratigan, J.L., "Radioactive Waste Repository Study - Topical Report 11 Room Stability" Submitted to Atomic Energy of Canada Limited, 1977.
5. Mahtab, M.A., Ratigan, J.L. and McCreath, D.R., "Stability of a Radioactive Waste Repository in the Canadian Shield", 18th Symposium on Rock Mechanics held at Keystone, Colorado, 1977.
6. Ratigan, J.L., "GROUNDWATER MOVEMENTS AROUND A REPOSITORY, Phase 2. Technical Report 2. Thermal Analysis - Part I: Conduction Heat Transfer", Submitted to KBS - Kärnbränslesäkerhet, Stockholm, Sweden., 1977.
7. Nayak, G.C. and Zienkiewicz, O.C., "Elasto-Plastic Stress Analysis - Generalization for Various Constitutive Relations Including Strain Softening", Int. J. Num.Meth.Eng., Vol.5, pp. 113-135, 1972.
8. Lundegårdh, P.H., Lundqvist, J. and Lindström, M. Berg och Jord I Sverige, Almqvist & Wiksell Läromedel AB, Stockholm, 1964.

TABLE 1

ROCK MASS PROPERTIES AND
In Situ Conditions

CASE No.	ρ (Kg/m ³)	E^1 (Kg/cm ²)	ν	α (°C ⁻¹)	β^2	^{1, 3} c_R (Kg/cm ²)	^{1, 4} c_J (Kg/cm ²)	⁵ ϕ_R	⁶ ϕ_J	⁷ K_o
1	2700	.214(10^6) ($2.1(10^4)$)	.25	$8(10^{-6})$	0° & 90°	10.2 (1)	10.2 (1)	34°	34°	2
2	2700	.214(10^6) ($2.1(10^4)$)	.25	$8(10^{-6})$	45° & -45°	10.2 (1)	10.2 (1)	34°	34°	2

- Notes:
1. Numbers in parenthesis are MPa.
 2. Angles of joint set orientations
 3. Cohesion or direct shear strength of intact rock
 4. Cohesion or direct shear strength of joint (Residual strength = 3.3 Kg/cm² (.3 MPa))
 5. Internal angle of friction for intact rock
 6. Internal angle of friction for joint (Residual = 30°)
 7. Ratio of in situ horizontal stress to vertical stress




FIGURE 1. LOCAL ROCK MECHANICS MODEL

NOTE: REGIONS OF STRENGTH
FAILURE INDICATED
WITH SHADING

SCALE:

0 0.5 1.0 m

FIGURE 2. REGIONS OF STRENGTH FAILURE DUE TO EXCAVATION IN A
ROCK MASS WITH JOINTS AT 0° AND 90° .

NOTE: REGIONS OF STRENGTH
FAILURE INDICATED
WITH SHADING

S C A L E:




FIGURE 3. REGIONS OF STRENGTH FAILURE DUE TO EXCAVATION IN A
ROCK MASS WITH JOINTS AT 45° AND -45° .




FIGURE 4. PRINCIPLE STRESSES RESULTING FROM EXCAVATION IN A ROCK MASS WITH $K_0 = 2$ AND JOINTS AT 0° AND 90° .




FIGURE 5. PRINCIPLE STRESSES RESULTING FROM EXCAVATION IN A ROCK MASS WITH
 $K_0 = 2$ AND JOINTS AT 45° AND -45° .






FIGURE 6. PROGRESSIVE STRENGTH FAILURE DUE TO EXCAVATION AND THERMOMECHANICAL STRESSES
WITH JOINTS AT 0° AND 90° .



SCALE:



NOTE: REGIONS OF STRENGTH FAILURE
INDICATED WITH SHADING

FIGURE 7. PROGRESSIVE STRENGTH FAILURE DUE TO EXCAVATION AND THERMOMECHANICAL STRESSES
WITH JOINTS AT 45° AND -45° .




FIGURE 8. IN SITU, POST-EXCAVATION AND THERMOMECHANICAL STRESSES IN THE STORAGE TUNNEL ROOF.




FIGURE 9. IN SITU, POST-EXCAVATION AND THERMOECHANICAL STRESSES IN THE STORAGE TUNNEL RIB.




FIGURE 10. IN SITU, POST-EXCAVATION AND THERMOMECHANICAL STRESSES IN THE STORAGE TUNNEL FLOOR.




FIGURE 11. PROGRESSIVE STRENGTH FAILURE DUE TO EXCAVATION AND THERMOMECHANICAL STRESSES WITH JOINTS AT 0° AND 90° WITH 30 YEARS OF TUNNEL VENTILATION.




FIGURE 12. PROGRESSIVE STRENGTH FAILURE DUE TO EXCAVATION AND THERMOMECHANICAL STRESSES WITH JOINTS AT 45° AND -45° WITH 30 YEARS OF TUNNEL VENTILATION.





FIGURE 13. GLOBAL ROCK MECHANICS MODELS




FIGURE 14. DISPLACEMENT ACROSS THE EARTH'S SURFACE DUE TO ROCK MASS EXPANSION.




FIGURE 15. TRANSIENT DISPLACEMENT ABOVE THE REPOSITORY CENTERLINE




FIGURE 16. HORIZONTAL IN SITU AND THERMOECHANICAL STRESSES THROUGH THE REPOSITORY CENTERLINE

A P P E N D I X

FINITE ELEMENT MODELS




FIGURE A.1(A) FINITE ELEMENT MODEL FOR LOCAL ROCK MECHANICS ANALYSIS





FIGURE A.1(B) INSERT OF LOCAL ROCK MECHANICS MODEL




NOTE:

ALL ELEMENTS
ARE 8-NODED
ISOPARAMETRIC
QUADRILATERALS

FIGURE A.2 FINITE ELEMENT MODEL FOR 500 M REPOSITORY GLOBAL ROCK MECHANICS ANALYSIS

REPOSITORY CENTERLINE



NOTE:

- (1) ALL ELEMENTS
ARE 8-NODED
ISOPARAMETRIC
QUADRILATERALS

FIGURE A.4 SYMMETRIC HALF SECTION OF FINITE ELEMENT MODEL FOR 500 M LINEAR WASTE EMPLACEMENT REPOSITORY GLOBAL ROCK MECHANICS ANALYSIS.

FÖRTECKNING ÖVER KBS TEKNISKA RAPPORTER

- 01 Källstyrkor i utbränt bränsle och högaktivt avfall från en PWR beräknade med ORIGEN
Nils Kjellbert
AB Atomenergi 77-04-05
- 02 PM angående värmeläningstal hos jordmaterial
Sven Knutsson
Roland Pusch
Högskolan i Luleå 77-04-15
- 03 Deponering av högaktivt avfall i borrhål med buffertsubstans
Arvid Jacobsson
Roland Pusch
Högskolan i Luleå 77-05-27
- 04 Deponering av högaktivt avfall i tunnlar med buffertsubstans
Arvid Jacobsson
Roland Pusch
Högskolan i Luleå 77-06-01
- 05 Orienterande temperaturberäkningar för slutförvaring i berg av radioaktivt avfall, Rapport 1
Roland Blomqvist
AB Atomenergi 77-03-17
- 06 Groundwater movements around a repository, Phase I, State of the art and detailed study plan
Ulf Lindblom
Hagconsult AB 77-02-28
- 07 Resteffekt studier för KBS
Del 1 Litteraturgenomgång
Del 2 Beräkningar
Kim Ekberg
Nils Kjellbert
Göran Olsson
AB Atomenergi 77-04-19
- 08 Utlakning av franskt, engelskt och kanadensiskt glas med högaktivt avfall
Göran Blomqvist
AB Atomenergi 77-05-20

- 09 Diffusion of soluble materials in a fluid filling a porous medium
Hans Häggblom
AB Atomenergi 77-03-24
- 10 Translation and development of the BNWL-Geosphere Model
Bertil Grundfelt
Kemakta Konsult AB 77-02-05
- 11 Utredning rörande titans lämplighet som korrosionshärdig kapsling för kärnbränsleavfall
Sture Henriksson
AB Atomenergi 77-04-18
- 12 Bedömning av egenskaper och funktion hos betong i samband med slutlig förvaring av kärnbränsleavfall i berg
Sven G Bergström
Göran Fagerlund
Lars Rombén
Cement- och Betonginstitutet 77-06-22
- 13 Urlakning av använt kärnbränsle (bestrålad uranoxid) vid direktdeponering
Ragnar Gelin
AB Atomenergi 77-06-08
- 14 Influence of cementation on the deformation properties of bentonite/quartz buffer substance
Roland Pusch
Högskolan i Luleå 77-06-20
- 15 Orienterande temperaturberäkningar för slutförvaring i berg av radioaktivt avfall
Rapport 2
Roland Blomquist
AB Atomenergi 77-05-17
- 16 Översikt av utländska riskanalyser samt planer och projekt rörande slutförvaring
Åke Hultgren
AB Atomenergi augusti 1977
- 17 The gravity field in Fennoscandia and postglacial crustal movements
Arne Bjerhammar
Stockholm augusti 1977
- 18 Rörelser och instabilitet i den svenska berggrunden
Nils-Axel Mörner
Stockholms Universitet augusti 1977
- 19 Studier av neotektonisk aktivitet i mellersta och norra Sverige, flygbildsgenomgång och geofysisk tolkning av recenta förkastningar
Robert Lagerbäck
Herbert Henkel
Sveriges Geologiska Undersökning september 1977

- 20 Tektonisk analys av södra Sverige, Vättern - Norra Skåne
Kennert Röshoff
Erik Lagerlund
Lunds Universitet och Högskolan Luleå september 1977
- 21 Earthquakes of Sweden 1891 - 1957, 1963 - 1972
Ota Kulhánek
Rutger Wahlström
Uppsala Universitet september 1977
- 22 The influence of rock movement on the stress/strain
situation in tunnels or bore holes with radioactive con-
sisters embedded in a bentonite/quartz buffer mass
Roland Pusch
Högskolan i Luleå 1977-08-22
- 23 Water uptake in a bentonite buffer mass
A model study
Roland Pusch
Högskolan i Luleå 1977-08-22
- 24 Beräkning av utlakning av vissa fissionsprodukter och akti-
nider från en cylinder av franskt glas
Göran Blomqvist
AB Atomenergi 1977-07-27
- 25 Blekinge kustgnejs, Geologi och hydrogeologi
Ingemar Larsson KTH
Tom Lundgren SGI
Ulf Wiklander SGU
Stockholm, augusti 1977
- 26 Bedömning av risken för fördröjt brott i titan
Kjell Pettersson
AB Atomenergi 1977-08-25
- 27 A short review of the formation, stability and cementing
properties of natural zeolites
Arvid Jacobsson
Högskolan i Luleå 1977-10-03
- 28 Värmeledningsförsök på buffertsubstans av bentonit/pitesilt
Sven Knutsson
Högskolan i Luleå 1977-09-20
- 29 Deformationer i sprickigt berg
Ove Stephansson
Högskolan i Luleå 1977-09-28
- 30 Retardation of escaping nuclides from a final depository
Ivars Neretnieks
Kungliga Tekniska Högskolan Stockholm 1977-09-14
- 31 Bedömning av korrosionsbeständigheten hos material avsedda
för kapsling av kärnbränsleavfall. Lägesrapport 1977-09-27
samtid kompletterande yttranden.
Korrosionsinstitutet och dess referensgrupp

- 32 Long term mineralogical properties of bentonite/quartz
buffer substance
Preliminär rapport november 1977
Slutrapport februari 1978
Roland Pusch
Arvid Jacobsson
Högskolan i Luleå
- 33 Required physical and mechanical properties of buffer masses
Roland Pusch
Högskolan Luleå 1977-10-19
- 34 Tillverkning av bly-titan kapsel
Folke Sandelin AB
VBB
ASEA-Kabel
Institutet för metallforskning
Stockholm november 1977
- 35 Project for the handling and storage of vitrified high-level
waste
Saint Gobain Techniques Nouvelles October, 1977
- 36 Sammansättning av grundvatten på större djup i granitisk
berggrund
Jan Rennerfelt
Orrje & Co, Stockholm 1977-11-07
- 37 Hantering av buffertmaterial av bentonit och kvarts
Hans Fagerström, VBB
Björn Lundahl, Stabilator
Stockholm oktober 1977
- 38 Utformning av bergrumsanläggningar
Arne Finné, KBS
Alf Engelbrektson, VBB
Stockholm december 1977
- 39 Konstruktionsstudier, direktdeponering
ASEA-ATOM
VBB
Västerås
- 40 Ekologisk transport och stråldoser från grundvattenburna
radioaktiva ämnen
Ronny Bergman
Ulla Bergström
Sverker Evans
AB Atomenergi
- 41 Säkerhet och strålskydd inom kärnkraftområdet.
Lagar, normer och bedömningsgrunder
Christina Gyllander
Siegfried F Johnson
Stig Rolandson
AB Atomenergi och ASEA-ATOM

- 42 Säkerhet vid hantering, lagring och transport av använt kärnbränsle och förglasat högaktivt avfall
Ann Margret Ericsson
Kemakta november 1977
- 43 Transport av radioaktiva ämnen med grundvatten från ett bergförrvar
Bertil Grundfelt
Kemakta november 1977
- 44 Beständighet hos borsilikatglas
Tibor Lakatos
Glasteknisk Utveckling AB
- 45 Beräkning av temperaturer i ett envånings slutförvar i berg för förglasat radioaktivt avfall Rapport 3
Roland Blomquist
AB Atomenergi 1977-10-19
- 46 Temperaturberäkningar för använt bränsle
Taivo Tahrandi
VBB
- 47 Teoretiska studier av grundvattenrörelser
Preliminär rapport oktober 1977
Slutrapport februari 1978
Lars Y Nilsson
John Stokes
Roger Thunvik
Inst för kulturtexnik KTH
- 48 The mechanical properties of Stripa granite
Graham Swan
Högskolan i Luleå 1977-09-14
- 49 Bergspänningsmätningar i Stripa gruva
Hans Carlsson
Högskolan i Luleå 1977-08-29
- 50 Lakningsförsök med högaktivt franskt glas i Studsvik
Göran Blomqvist
AB Atomenergi november 1977
- 51 Seismotectonic risk modelling for nuclear waste disposal in the Swedish bedrock
F Ringdal
H Gjøystdal
E S Husebye
Royal Norwegian Council for scientific and industrial research
- 52 Calculations of nuclide migration in rock and porous media, penetrated by water
H Häggblom
AB Atomenergi 1977-09-14

- 53 Mätning av diffusionshastighet för silver i lera-sand-blandning
Bert Allard
Heino Kipatsi
Chalmers tekniska högskola 1977-10-15
- 54 Groundwater movements around a repository
- 54:01 Geological and geotechnical conditions
Håkan Stille
Anthony Burgess
Ulf E Lindblom
Hagconsult AB september 1977
- 54:02 Thermal analyses
Part 1 Conduction heat transfer
Part 2 Advective heat transfer
Joe L Ratigan
Hagconsult AB september 1977
- 54:03 Regional groundwater flow analyses
Part 1 Initial conditions
Part 2 Long term residual conditions
Anthony Burgess
Hagconsult AB oktober 1977
- 54:04 Rock mechanics analyses
Joe L Ratigan
Hagconsult AB september 1977
- 54:05 Repository domain groundwater flow analyses
Part 1 Permeability perturbations
Part 2 Inflow to repository
Part 3 Thermally induced flow
Joe L Ratigan
Anthony S Burgess
Edward L Skiba
Robin Charlwood
- 54:06 Final report
Ulf Lindblom et al
Hagconsult AB oktober 1977
- 55 Sorption av långlivade radionuklider i lera och berg
Del 1 Bestämning av fördelningskoefficienter
Del 2 Litteraturgenomgång
Bert Allard
Heino Kipatsi
Jan Rydberg
Chalmers tekniska högskola 1977-10-10
- 56 Radiolys av utfyllnadsmaterial
Bert Allard
Heino Kipatsi
Jan Rydberg
Chalmers tekniska högskola 1977-10-15

- 57 Stråldoser vid haveri under sjötransport av kärnbränsle
Anders Appelgren
Ulla Bergström
Lennart Devell
AB Atomenergi
- 58 Strålrisker och högsta tillåtliga stråldoser för människan
Gunnar Walinder
AB Atomenergi